

TrueNAS® Expansion Shelves

SCALE STORAGE EFFORTLESSLY

To meet the demands of today's applications, businesses need to keep pace with massive data growth. The modern business has to support a full range of storage protocols for Windows, Apple, Unix, and mobile devices. Thousands of terabytes of data needs to be retained for analysis by Big Data applications.

To support these and other business requirements, and to reduce storage sprawl, the TrueNAS "pay as you grow" pricing model offers storage, power, and space efficiency with the ability to expand capacity on an as-needed basis.

Three expansion shelf options make TrueNAS capacity expansion effortless for businesses that never sleep. Every TrueNAS model has enclosure management, supports storage controller redundancy and global hot spares, zero-downtime firmware updates, upgrades, and offers around the clock support. Without disruption, you can add expansion shelves and drives to TrueNAS to keep pace with growing storage needs.



HARDWARE SPECIFICATIONS

AVAILABLE EXPANSION SHELVES

TRUENAS ES12

- 2U: 12x 3.5"/2.5" hard drive bays (front-loading, hot swap)
- Redundant, hot-swap SAS3 (12Gb/s) controllers
- 3x Mini-SAS HD Host Connections Per Controller (SFF-8644)
- Physical Dimensions (length x width x height):
 - 21 x 19 x 3.5" | 531 x 447 x 89mm
- Rackmount Rails Depth: 23.5" to 29.5" standard, up to 36" with extenders (incl.)
- Empty weight: 26 lbs | 12 kg
- Fully-loaded weight: 44 lbs | 20 kg
- Power Draw: 112W (idle); 180W (max)

TRUENAS ES24

- 4U: 24x 3.5"/2.5" hard drive bays (front-loading, hot swap)
- Redundant, hot-swap SAS3 (12Gb/s) controllers
- 3x Mini-SAS HD Host Connections Per Controller (SFF-8644)
- Physical Dimensions (length x width x height):
 - 20.5 x 19 x 7" | 521 x 483 x 178mm
- Rackmount Rails Depth: 26.5 to 36.5"
- Empty weight: 40 lbs | 18 kg
- Fully-loaded weight: 76 lbs | 34.5 kg
- Power Draw: 231W (idle); 288W (max)

TRUENAS ES60

- 4U: 60x 3.5"/2.5" hard drive bays (top-loading, hot swap)
- Redundant, hot-swap SAS3 (12Gb/s) controllers
- 2x Mini-SAS HD Host Connections Per Controller (SFF-8644)
- Physical Dimensions (length x width x height):
 - 39.5 x 19 x 7" | 1004 x 424 x 176mm
- Rackmount Rails Depth w/ Cable Management Arm: 27.5" to 30"
- Rackmount Rails Depth w/o Cable Management Arm: 27.5" to 38.5"
- Empty weight: 85 lbs | 38.5 kg
- Fully-loaded weight: 175 lbs | 80 kg
- Power Draw w/ 60 HDDs: 479W (idle); 821W (max)

AVAILABLE STORAGE MEDIA

- Enterprise Nearline Hard Drives (7200 RPM SAS3 - 12Gb/s):
 - Capacities available from 2TB to 14TB
 - (Self-Encrypting Drives (SED) Available)
- Enterprise Solid State Drives (SAS3 - 12Gb/s):
 - Capacities available from 250GB to 7.68TB
 - (Self-Encrypting Drives (SED) Available)

POWER MANAGEMENT

- Redundant, hot-swappable high-efficiency (90%+) power supplies
- 100-240 Volt input power supported (auto-switching)
- UPS signal response and alerts
- Redundant cooling
- All expansion shelves are RoHS 6/6 compliant

	Max Capacity			
	Base Unit	ES12	ES24	ES60
TrueNAS X10	168TB	504TB (two shelves)	Not supported	
TrueNAS X20	168TB	504TB (two shelves)	Not supported	720TB (one shelf)
TrueNAS M40	336TB	672MB (two shelves)	1PB (two shelves)	2PB (two shelves)
TrueNAS M50	336TB	2.35PB (twelve shelves)	4.37PB (twelve shelves)	10.4PB (twelve shelves)
TrueNAS Z50	122TB	Not supported	860TB (four shelves)	Not Supported

855-GREP-4-IX (US) | 408-943-4100 (non-US) | ixsystems.com

ixsystems | 2490 Kruse Drive | San Jose, CA 95131

Copyright © 2018 ixsystems. TrueNAS is a registered trademark of ixsystems, Inc. All rights reserved.

